

**MATERIAL SAFETY DATA SHEET**

REVISION DATE: 05-01-2012

SUPERSEDES: 09-16-2009

**SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION****COMPANY INFORMATION**

H.B. Fuller Construction Products Inc.  
1105 S. Frontenac Street  
Aurora, IL 60504  
Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**PRODUCT INFORMATION**

PRODUCT NUMBER: FOSTER 85-15  
PRODUCT NAME: FOSTER 85-15  
PRODUCT DESCRIPTION: Adhesive  
PRODUCT IDENTIFIER: 802413PM

**SECTION 2: HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

PHYSICAL STATE: Liquid  
COLOR: Yellow  
ODOR: Solvent

Extremely flammable.  
Moderate to severe eye irritant.  
Causes skin irritation.  
Moderate respiratory tract irritant.  
Harmful if swallowed.

**POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY**

**EYE:** Eye contact may cause moderate to severe eye irritation. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

**SKIN:** Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

**INHALATION:** Can cause moderate respiratory irritation.

Inhalation of vapors may cause loss of feeling and weakness in the hands and feet and loss of manual dexterity. Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination.

**INGESTION:** Ingestion is not an anticipated route of exposure. Harmful if swallowed. Irritating to mouth, throat, and stomach.

**LONG-TERM (CHRONIC) HEALTH EFFECTS**

**REPRODUCTIVE:** Contains a substance that is a possible reproductive hazard based on animal studies.

**TARGET ORGAN(S):** Central nervous system Peripheral nervous system Reproductive system Liver

**REGULATED CARCINOGEN STATUS:**

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

**EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE:** Liver disease

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**MATERIAL SAFETY DATA SHEET**

Chemical Name	CAS #	PERCENT
Hexane, n	110-54-3	30 - 50
Toluene	108-88-3	10 - 30

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

**SECTION 4: FIRST AID MEASURES**

**IF IN EYES:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

**IF ON SKIN:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

**IF VAPORS INHALED:** Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

**IF SWALLOWED:** Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

**SECTION 5: FIRE FIGHTING MEASURES**

FLASH POINT:	-18C; 0F TCC
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Vapors are heavier than air and can travel to a source of ignition and flash back.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**SPECIAL PROTECTION:** Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

**CLEAN-UP:** Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.  
Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 7: HANDLING AND STORAGE**

**Handling:** Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area.

## MATERIAL SAFETY DATA SHEET

---

Keep away from heat, sparks and flame.  
 Wash thoroughly after handling.  
 Keep container closed.  
 Emptied container retains vapor and product residue.  
 Observe all labeled precautions until container is cleaned.  
 Drums of this material should be grounded when pouring.  
**DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.**

**Storage:** Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and other sources of ignition. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

**EYE PROTECTION:** Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.

**SKIN PROTECTION:** Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.

**GLOVES:** Nitrile

**RESPIRATORY PROTECTION:** Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with organic vapor cartridge. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

**VENTILATION:** Use local exhaust ventilation or other engineering controls to minimize exposures.

#### **EXPOSURE LIMITS:**

<b>Chemical Name</b>	<b>ACGIH EXPOSURE LIMITS</b>	<b>OSHA PEL</b>
Hexane, n	50 ppm TWA Skin absorption may potentially contribute to the overall exposure to this material.	500 ppm TWA; 1800 mg/m <sup>3</sup> TWA
Toluene	20 ppm TWA	200 ppm TWA 300 ppm Ceiling

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

**PHYSICAL STATE:** Liquid  
**COLOR:** Yellow  
**ODOR:** Solvent  
**ODOR THRESHOLD:** Not established  
**WEIGHT PER GALLON (lbs.):** 6.60  
**SPECIFIC GRAVITY:** 0.790  
**SOLIDS (% by weight):** 38.6  
  
**pH:** Not established

**MATERIAL SAFETY DATA SHEET**

FLASH POINT: -18C; 0F TCC  
BOILING POINT (deg. C): Not established  
FREEZING/MELTING POINT (deg. C): Not established  
VAPOR PRESSURE (mm Hg): Not established  
VAPOR DENSITY: Not established  
EVAPORATION RATE: Not established  
OCTANOL/WATER COEFFICIENT: Not established  
VOC, weight percent 61.70  
VOC, EPA Method 24, less water and exempt solvents 487g/liter of material  
(theoretically determined)

**SECTION 10: STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions.  
CHEMICAL INCOMPATIBILITY: Strong oxidizing agents  
HAZARDOUS POLYMERIZATION: Will not occur.  
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

**SECTION 11: TOXICOLOGICAL INFORMATION**

COMPONENT	LD50/LC50
Hexane, n	Oral LD50 Rat = 28,710 mg/kg Inhalation LC50 Rat = 48,000 ppm/4H
Toluene	Oral LD50 Rat = 636 mg/kg Inhalation LC50 Rat = 49,000 mg/cu m/4H Dermal LD50 Rabbit = 14 ml/kg

TOXICOLOGY SUMMARY: No additional health information available.

**SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available

**SECTION 13: DISPOSAL CONSIDERATIONS**

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Toluene

**SECTION 14: TRANSPORTATION INFORMATION**

Consult Bill of Lading for transportation information.

DOT: UN1133, ADHESIVES, 3, II

IATA: UN1133, ADHESIVES, 3, II

**SECTION 15: REGULATORY INFORMATION****INVENTORY STATUS**

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.  
CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.  
EUROPEAN EINECS: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.  
AUSTRALIA AICS: This product is in compliance with the Australian Inventory of Chemical Substances requirements.  
KOREAN TCCL: This product is in compliance with the Korean Existing Chemicals List

**MATERIAL SAFETY DATA SHEET**

requirements.  
PHILIPPINES: This product is in compliance with the Philippine Inventory of Chemicals and Chemical Substances requirements.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

**FEDERAL REPORTING**

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
n-Hexane	110-54-3	30 - 50
Toluene	108-88-3	10 - 30

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

B2

D2B D2A

**STATE REPORTING**

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Benzene (Carcinogen)	71-43-2	0.001 - 0.01
Toluene (Developmental toxin)	108-88-3	10 - 30
Benzene (Developmental toxin)	71-43-2	0.001 - 0.01
Benzene, methyl- (Female reproductive toxin)	108-88-3	10 - 30
Benzene (Male reproductive toxin)	71-43-2	0.001 - 0.01

**SECTION 16: ADDITIONAL INFORMATION**

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 3 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is

## MATERIAL SAFETY DATA SHEET

---

the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.