

# MATERIAL SAFETY DATA SHEET

Effective Date: March 1, 2007

## SECTION I PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME(S) OR NUMBER(S) DAXCEL <sup>®</sup> FOAMASTIK <sup>®</sup> 161-D Adhesive	EMERGENCY PHONE NUMBERS Chemtrec <sup>®</sup> 800-424-9300 (Inside US) 703-527-3887 (Outside US) Supplier 412-922-2536	
MANUFACTURER/SUPPLIER/NAME/ADDRESS Dacar Products Company Inc. 1019 McCartney Street Pittsburgh, PA 15220	IMO & IATA HAZARD DESIGNATION PROPER NAME / CLASS / NUMBER / PKG GROUP / RQ Adhesive, 3.3, UN 1133, III (containing less than 5% Naphtha, Petroleum)	
CHEMICAL FAMILY Oil-based Adhesive	FORMULA See Section II	DOT DOMESTIC US GROUND TRANSPORT HAZARD DESIGNATION Unregulated

### HAZARD RATINGS

	NPCA-HMIS	KEYS	
Health	0	4 = Severe	1 = Slight
Flammability	2	3 = Serious	0 = Minimal
Reactivity	0	2 = Moderate	N = None (see Section VIII)
Personal Protection	N		

## SECTION II CHEMICAL COMPONENTS

CHEMICAL NAME	TLV	CAS NOS.	PCT.
Calcium Carbonate	N/A	471-34-1	60-70
Magnesium Carbonate	N/A	546-93-0	4-10
Linseed Oil	N/A	8001-26-1	4-10
Soybean Oil	N/A	68152-81-8	4-10
Petroleum Naphtha Mixture	500 ppm	8742-88-7 / 64742-47-8	4-10

(N/A = Not Available)

## SECTION III PHYSICAL DATA

Boiling Point (°C / °F)	> 127 / 261	Solubility in Water	Negligible
Vapor Pressure (@ 20°C)	N/A	Specific Gravity	1.8
Vapor Density (air = 1)	N/A	Evaporation Rate	
Volatile Organic Content (g / l)	< 80	(Ethyl ether = 1)	N/A
APPEARANCE Heavy Mastic, Light Gray	ODOR Mild Odor	MATERIAL IS A Paste	

## SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Closed Cup) 40°C / 104°F (Pensky Martin)	LEL 1.4*	UEL 8.1*	IGNITION TEMPERATURE 216°C / 421°F*	EXTINGUISHING MEDIA Regular Foam or Carbon Dioxide
--	-------------	-------------	--	---

\*Solvent Only

SPECIAL FIRE FIGHTING PROCEDURES  
None

UNUSUAL FIRE AND EXPLOSION HAZARDS  
None

## SECTION V PHYSIOLOGICAL EFFECTS

### EFFECTS OF EXPOSURE

Eyes: May cause irritation  
 Skin: May cause irritation and contact dermatitis in sensitive persons  
 Inhalation: May cause lightheadedness  
 Swallowing: May cause irritation, nausea, vomiting or diarrhea

### EMERGENCY AND FIRST AID PROCEDURES

Eyes: Flush with large amounts of water; get medical attention  
 Skin: Wash thoroughly with soap and water  
 Inhalation: Remove to fresh air  
 Swallowing: Drink two glasses of water and induce vomiting; get medical attention

## SECTION VI REACTIVITY DATA

MATERIALS IS	CONDITIONS TO AVOID	MATERIALS TO AVOID	DECOMPOSITION PRODUCTS
Stable	Heat, flame and fire	None	Carbon dioxide/monoxide

### HAZARDOUS POLYMERIZATION

Will Not Occur

### CONDITIONS TO AVOID

Avoid open flame or sparks

## SECTION VII SPILL OR LEAK PROCEDURES

### SMALL SPILL

Absorb residue on floor absorbent or similar material; dispose of absorbent properly.

### LARGE SPILL

Material may be shoveled into proper containers. Residue may be absorbed by clay, sand, floor absorbent or similar materials and shoveled into containers.

### WASTE DISPOSAL METHOD

Dispose of in accordance with all Federal, State and Local laws and regulations.

## SECTION VIII PROTECTIVE EQUIPMENT

Ventilation: Generally none. For prolonged exposure in small, closed space, general ventilation.  
 Respiratory: None.  
 For Eyes: Generally none; product will not splash easily. If needed, use any type splash goggles.  
 For Skin: Generally none; for prolonged skin contact, wear natural rubber gloves.

## SECTION IX SPECIAL PRECAUTIONS

Container may contain liquid or vapor residue. Do not cut container with torch. Obey all precautions until container disposed of. Do not reuse container. Dispose of container in accordance with Federal, State and Local regulations.

CHANGES since last version: None.