



NASHUA® 398
Premium Grade Duct Tape


APPLICATIONS

- Home and general repair.
- Bundling, patching, and mending.
- HVAC industry to duct and equipment applications
- High quality maintenance tape for a variety of manufacturing environments.
- Asbestos removal and PE hanging.

FEATURES & BENEFITS

- High quality polyethylene coated cloth.
- Conforms well to irregular surfaces.
- Adheres to a wide variety of substrates.
- Tears straight, hangs straight, and curl resistant.
- Easy unwind.
- Tested in accordance with UL 723.

CONSTRUCTION



PRODUCT DESCRIPTION

Single-Coated Construction

Backing:

- Polyethylene Coated Cloth

Adhesive:

- Rubber

Colors:

- Black, Blue, Green, Burgundy, Olive Drab, Red, Yellow, White, Silver

TEST DATA

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness	11 mils	279.40 μ	ASTM D 1000
Adhesion to Steel	47 oz./in.	5.14 N/cm	PSTC-1
Adhesion to Backing	46 oz./in.	5.03 N/cm	PSTC-1
Tensile Strength	27 lb./in.	47.28 N/cm	ASTM D 1000
Unwind Force	62 oz./in.	6.786 N/cm	ASTM D 1000
Maximum Performance Temperature	200 F		
Flame Spread	10		
Smoke Developed	10		

**Recommended storage conditions: 40-60% Humidity, 60°F-80°F

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical person. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any responsibility.