

Fiber Free



# AP/Armaflex<sup>®</sup>

Sheet & Roll Insulation

## Superior Moisture Control on Large Jobs, Mold Resistant



- Fiber Free, Closed Cell, Non-Wicking
- GREENGUARD Children & Schools Certified<sup>®</sup>
- Made with Microban<sup>®</sup> Antimicrobial Product Protection
- Thicknesses up to 2" Wall
- 25/50 Rated Through 1" Wall
- 25/50 Rated through 2" wall available in AP Armaflex FS  
*(see AP Armaflex FS submittal form)*



## AP Armaflex Sheet & Roll Insulation

**AP Armaflex Sheet and Roll Insulation** is the original closed cell, fiber-free elastomeric foam and the world's most recognized brand in flexible mechanical insulation.

- **Proven:** World's first choice for insulating ductwork, large piping, fittings, tanks, vessels and curved or irregular surfaces
- **Mold resistant:** Made with Microban antimicrobial product protection
- **Indoor Air Quality-friendly:** Fiber-free, formaldehyde-free, low VOCs, nonparticulating. GREENGUARD Indoor Air Quality Certified®.
- **Quiet:** Noise blocking and vibration damage
- **Durable:** No fragile vapor retarder

### Description

**AP Armaflex Sheet and Roll Insulation** is a black flexible elastomeric thermal insulation. It is furnished with a smooth skin on one side only or both sides which forms the outer exposed insulation surface. The expanded closed-cell structure makes it an efficient insulation. It is manufactured without the use of CFC's, HFC's or HCFC's. All AP Armaflex products are made with Microban® antimicrobial product protection for added defense against mold on the insulation. It is also effective for reducing HVAC noise.

- **AP Armaflex Sheet** is supplied in flat sheets 36" x 48" (.915m x 1.22) in nominal wall thicknesses of 1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/2" and 2" (3, 6, 10, 13, 19, 25, 38 and 50mm).
- **AP Armaflex Roll** is supplied in 48" wide (1.22m) continuous rolls in nominal wall thicknesses of 3/8", 1/2", 3/4", 1", 1-1/2" and 2" (10, 13, 19, 25, 38 and 50mm). Also available in 60" (1.53m).
- **AP Armaflex FS Sheet and Roll** available in 25/50 for 1-1/2" and 2" thicknesses - See AP Armaflex FS submittal.

### Factory Mutual (FM) Approvals

AP Armaflex is approved through continuing supervision by Factory Mutual Approvals to consistently provide actual values on these key performance criteria for mechanical system insulation through 1" (25mm):

- **Thermal Conductivity:** 0.25 BTU-in/hr. ft<sup>2</sup> °F
- **Water Vapor Transmission:** 0.05 perm-inch
- **Fire Rating:** will not contribute significantly to fire (simulated end-use testing)

As tested by ASTM E 84 "Method of Test for Surface Burning Characteristics for Building Materials," AP Armaflex in wall thickness up to and including 1" (25mm) has a flame-spread index of less than 25 and a smoke-developed index of less than 50.

*Note: Numerical flammability ratings alone may not define the performance of products under actual fire conditions. They are provided only for use in the selection of products to meet limits specified.*

### Uses

- Retards heat gain and controls condensation drip from chilled-water and refrigeration systems. Efficiently reduces heat flow on hot systems
- Acceptable in wall thicknesses through 1" (25mm) for use in air plenums and conforms to NFPA 90A and NFPA 90B requirements

The recommended temperature usage range for AP Armaflex Sheet & Roll Insulation is -297°F to +220°F (-183°C to +105°C) according to method of application. With full adhesive coverage attachment, the surface to which it is applied may operate to a limit of 180°F (82°C). When used for pipe insulation with adhesive adhering seams and joints only, AP Armaflex Sheet can be applied to lines that will operate to a limit of 220°F (105°C).

AP Armaflex Sheet and Roll Insulation meets the energy code requirements of International Energy Conservation Code (IECC) and ASHRAE for **R-Value 4.2 at 1" wall thickness** and R-Value 8 at 2" wall thickness.

### Application

AP Armaflex Sheet and Roll is installed using one of our Armaflex adhesives: Armaflex 520, 520 Black or, where a low V.O.C. adhesive is required, Armaflex 520 BLV or Armaflex Spray Contact Adhesive. For application to large, flat or curved metal surfaces such as ducts, very large pipes, tanks and vessels, full adhesive coverage is used. For application as pipe insulation and fitting covers, only the seams and joints are adhered with Armaflex adhesive. 520 Adhesives are contact adhesives; therefore, in all cases, both surfaces to be joined are coated with adhesive. Exterior ductwork must be pitched to allow rainwater to run off the insulation.

For many applications, Armaflex needs no supplementary protection. Additional vapor-retarder protection may be necessary on very-low-temperature surfaces or piping where the insulation is exposed to continually high humidity conditions.

AP Armaflex is designed for installation above or below ground. For below ground applications, contact Armacell or see our Technical Bulletin No. 7 on our website, [www.armacell.com](http://www.armacell.com). Outdoors, a weather-resistant protective finish is to be applied and Armaflex WB Finish is recommended.

### Specification Compliance

**AP Armaflex Sheet & Roll Insulation developed to meet:**

ASTM C 534, Type II — Sheet Grade 1	MIL-P-15280J, FORM S MIL-C-3133C (MIL STD 670B), Grade SBE 3
ASTM C 1534	MEA 107-89M
ASTM E 84, NFPA 255, UL 723	UL 181
CAN/ULC S102	UL 94 5V-A, V-0, File E 55798
NFPA 90A, 90B	City of Los Angeles – RR 7642
ASTM G21/C1338	
ASTM G22	
ASTM D 1056, 2B1	

ALL ARMACELL FACILITIES  
IN NORTH AMERICA ARE  
ISO 9001:2008 CERTIFIED.

AP Armaflex Sheet & Roll Insulation

[www.armacell.us](http://www.armacell.us)

For the latest document, please refer to our website.

## Physical Properties

Specifications	Values	Test Method
<b>Thermal Conductivity, Btu • in./h • ft<sup>2</sup> • °F (W/mK)</b> 75°F Mean Temperature (24°C) 90°F Mean Temperature (32°C)	0.25 (0.036) 0.256 (0.037)	ASTM C 177 or C 518
<b>Water Vapor Permeability, Perm-in. [Kg/(s•m•Pa)]</b>	0.05 (0.725 x 10 <sup>-19</sup> )	ASTM E 96, Procedure A
<b>Flame Spread and Smoke Developed Index through 1" (25mm)*</b>	25/50*	ASTM E 84 CAN/ULC S102
<b>Mold Growth Fungi Resistance Bacterial Resistance</b>	UL181 ASTM G21/C1338 ASTM G22	Meets requirements Meets requirements Meets requirements
<b>Water Absorption, % by Volume</b>	0.2%	ASTM C 209
<b>Upper Use Limit ①</b>	180/220°F (82/105°C)	—
<b>Lower Use Limit ②</b>	-297°F (-183°C)**	—
<b>Ozone Resistance</b>	GOOD	—
<b>Sizes – Sheet Width and Length Thickness (nominal)</b>	36" x 48" (.915m x 1.22m) 1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/2"* & 2"* (3, 6, 10, 13, 19, 25, 38 & 50mm)	—
<b>Sizes – Roll Width Thickness (nominal) x Length</b>	48" (1.22mm) and 60" (1.53m) 3/8" x 100' (10mm x 30.5m) 1/2" x 70' (13mm x 21.4m) 3/4" x 50' (19mm x 15.2m) 1" x 35' (25mm x 10.7m) 1-1/2"* x 25' (38mm x 7.6m) 2"* x 18' (50mm x 5.4m)	—

### Notes

① When AP Armaflex Sheet is installed by adhering butt joints and seams only, the upper temperature limit is 220°F (105°C) using 520, 520 black, or 520 BLV Adhesive.

AP Armaflex Sheet adhered with complete adhesive coverage on flat or curved metal surfaces may be applied to surfaces that will operate as high as 180°F (82°C) using 520, 520 Black, 520 BLV or Armaflex Low VOC Spray Contact Adhesive.

② At temperatures below -20°F (-29°C), elastomeric insulation starts to become less flexible. However, this characteristic does not affect thermal efficiency or water vapor permeability of Armaflex insulation.

\* For 25/50 above 1" (25mm). Please see AP Armaflex FS submittal. 1-1/2" and 2" available in 25/50 and non 25/50.

\*\* For applications of -40°F to -297°F (-40°C to -183°C), contact Armacell.

**ARMACELL LLC**

TEL: 1 800 866-5638

FAX: 919 304-3847

info.us@armacell.com

www.armacell.us

7600 Oakwood Street Extension • Mebane, NC 27302



Armacell provides this information as a technical service. To the extent the information is derived from sources other than Armacell, Armacell is substantially, if not wholly, relying upon the other source(s) to provide accurate information. Information provided as a result of Armacell's own technical analysis and testing is accurate to the extent of our knowledge and ability, as of date of printing, using effective standardized methods and procedures. Each user of these products, or information, should perform their own tests to determine the safety, fitness and suitability of the products, or combination of products, for any foreseeable purposes, applications and uses by the user and by any third party to which the user may convey the products. Since Armacell cannot control the end use of this product, Armacell does not guarantee that the user will obtain the same results as published in this document. The data and information are provided as a technical service and are subject to change without notice.

The GREENGUARD Children & Schools Certified Mark is a registered certification mark used under license through the GREENGUARD Environmental Institute.

Microban is a registered trademark of Microban Products Company.