

1583CW

GYMGUARD REINFORCED METALIZED WHITE POLYPROPYLENE FACING TAPE

DESCRIPTION: Metalized white polypropylene reinforced with a fiber-glass/polyester blend fabric coated with Venture's C.W. cold weather acrylic adhesive system. Specifically designed as a patch tape for high impact applications, i.e., hockey arenas, gymnasiums, tennis courts, etc. Excellent strength and tear resistance.

APPLICATIONS: Matches Lamtec Gymguard for wall and ceiling applications offering a smooth, bright white finish and a continuous vapor barrier.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
THICKNESS: (<i>excluding liner</i>)	6.5 mils (.0065")	0.165 mm
ADHESION:		
Peel (PSTC #1):	65 oz./in. width	18.4 N/2.5cm
Shear (PSTC #7): 100+ hrs @	2.2 psi	15.2 kPa
TENSILE (ASTM D-828):		
Machine Direction:	195 lbs./in. width	883.1 N/2.5cm
Transverse Direction:	150 lbs./in. width	679.0 N/2.5cm
MULLIN BURSTING		
STRENGTH (ASTM D-774):	250 psi minimum	1725 kPa
TEMPERATURE RESISTANCE:	-30°F to 250°F	-38°C to 121°C
MINIMUM APPLICATION		
TEMPERATURE:	-15°F	-26°C
WVTR (ASTM E-96 Proc. A):	0.02 perms maximum	
RELEASE LINER:	46 lb	75 GSM
	silicone coated natural kraft	

IMPORTANT INFORMATION:

The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using the product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

7-28-94